

# MEDICAL CASTER WITH CENTRAL CONTROL C21 Series

Capacity up to **160 kgs**



WhatsApp



WeChat

| Photo                                                                              | Model       | Size | Remark | Wheel Diameter (mm) | Wheel Width (mm) | Loading Capacity (kgs) | Mounting Height (mm) | Tread Material | Housing Material | Bearing Type        | Locking Functions                                              | Cam Locking Angle | Thread/Stem/Hole Size (mm) |
|------------------------------------------------------------------------------------|-------------|------|--------|---------------------|------------------|------------------------|----------------------|----------------|------------------|---------------------|----------------------------------------------------------------|-------------------|----------------------------|
|   | SCC2105-01S | 5.0" |        | 125                 | 60               | 100                    | 160                  | TPR            | Aluminum Alloy   | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel | 45°               | Φ32x50                     |
|                                                                                    | SCC2106-01S | 6.0" |        | 150                 | 60               | 130                    | 185                  |                |                  |                     |                                                                | 45°               | Φ32x50                     |
|  | SCC2105-01L | 5.0" |        | 125                 | 60               | 100                    | 160                  | TPR            | Aluminum Alloy   | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel | 45°               | Φ28x98.5                   |
|                                                                                    | SCC2106-01L | 6.0" |        | 150                 | 60               | 130                    | 185                  |                |                  |                     |                                                                | 45°               | Φ28x98.5                   |

# MEDICAL CASTER WITH CENTRAL CONTROL C21 Series

Capacity up to **160 kgs**



WhatsApp



WeChat

| Photo                                                                              | Model        | Size | Remark | Wheel Diameter (mm) | Wheel Width (mm) | Loading Capacity (kgs) | Mounting Height (mm) | Tread Material | Housing Material | Bearing Type        | Locking Functions                                                                      | Cam Locking Angle | Thread/Stem/Hole Size (mm) |
|------------------------------------------------------------------------------------|--------------|------|--------|---------------------|------------------|------------------------|----------------------|----------------|------------------|---------------------|----------------------------------------------------------------------------------------|-------------------|----------------------------|
|   | SCC2105-02DS | 5.0" |        | 125                 | 75               | 100                    | 153                  | TPU            | PA               | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel                         | 30°<br>or<br>45°  | Φ32x50                     |
|                                                                                    | SCC2106-02DS | 6.0" |        | 150                 | 76               | 130                    | 166                  |                |                  |                     |                                                                                        |                   |                            |
|                                                                                    | SCC2105-02TS | 5.0" |        | 125                 | 75               | 100                    | 153                  |                |                  |                     | Three Functions:<br>1. Free Swivel, 2.<br>Direction Lock, 3. Locks<br>Wheel and Swivel | 30°<br>or<br>45°  |                            |
|                                                                                    | SCC2106-02TS | 6.0" |        | 150                 | 76               | 130                    | 166                  |                |                  |                     |                                                                                        |                   |                            |
|  | SCC2105-02DL | 5.0" |        | 125                 | 75               | 100                    | 153                  | TPU            | PA               | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel                         | 30°<br>or<br>45°  | Φ28x96                     |
|                                                                                    | SCC2106-02DL | 6.0" |        | 150                 | 76               | 130                    | 166                  |                |                  |                     |                                                                                        |                   |                            |
|                                                                                    | SCC2105-02TL | 5.0" |        | 125                 | 75               | 100                    | 153                  |                |                  |                     | Three Functions:<br>1. Free Swivel, 2.<br>Direction Lock, 3. Locks<br>Wheel and Swivel | 30°<br>or<br>45°  |                            |
|                                                                                    | SCC2106-02TL | 6.0" |        | 150                 | 76               | 130                    | 166                  |                |                  |                     |                                                                                        |                   |                            |

# MEDICAL CASTER WITH CENTRAL CONTROL C21 Series

Capacity up to **160 kgs**



WhatsApp



WeChat

| Photo                                                                              | Model        | Size | Remark | Wheel Diameter (mm) | Wheel Width (mm) | Loading Capacity (kgs) | Mounting Height (mm) | Tread Material | Housing Material | Bearing Type        | Locking Functions                                                                      | Cam Locking Angle | Thread/Stem/Hole Size (mm) |
|------------------------------------------------------------------------------------|--------------|------|--------|---------------------|------------------|------------------------|----------------------|----------------|------------------|---------------------|----------------------------------------------------------------------------------------|-------------------|----------------------------|
|   | SCC2105-03DS | 5.0" |        | 125                 | 71.5             | 100                    | 154                  | TPR            | PA               | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel                         | 30°<br>or<br>45°  | Φ32x50                     |
|                                                                                    | SCC2106-03DS | 6.0" |        | 150                 | 79               | 130                    | 164                  |                |                  |                     |                                                                                        |                   |                            |
|                                                                                    | SCC2105-03TS | 5.0" |        | 125                 | 71.5             | 100                    | 154                  |                |                  |                     | Three Functions:<br>1. Free Swivel, 2.<br>Direction Lock, 3. Locks<br>Wheel and Swivel | 30°<br>or<br>45°  |                            |
|                                                                                    | SCC2106-03TS | 6.0" |        | 150                 | 79               | 130                    | 164                  |                |                  |                     |                                                                                        |                   |                            |
|  | SCC2105-03DL | 5.0" |        | 125                 | 71.5             | 100                    | 154                  | TPR            | PA               | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel                         | 30°<br>or<br>45°  | Φ28x96                     |
|                                                                                    | SCC2106-03DL | 6.0" |        | 150                 | 79               | 130                    | 164                  |                |                  |                     |                                                                                        |                   |                            |
|                                                                                    | SCC2105-03TL | 5.0" |        | 125                 | 71.5             | 100                    | 154                  |                |                  |                     | Three Functions:<br>1. Free Swivel, 2.<br>Direction Lock, 3. Locks<br>Wheel and Swivel | 30°<br>or<br>45°  |                            |
|                                                                                    | SCC2106-03TL | 6.0" |        | 150                 | 79               | 130                    | 164                  |                |                  |                     |                                                                                        |                   |                            |

# MEDICAL CASTER WITH CENTRAL CONTROL C21 Series

Capacity up to **160 kgs**



WhatsApp



WeChat

| Photo                                                                              | Model        | Size | Remark | Wheel Diameter (mm) | Wheel Width (mm) | Loading Capacity (kgs) | Mounting Height (mm) | Tread Material | Housing Material | Bearing Type        | Locking Functions                                                                      | Cam Locking Angle | Thread/Stem/Hole Size (mm) |
|------------------------------------------------------------------------------------|--------------|------|--------|---------------------|------------------|------------------------|----------------------|----------------|------------------|---------------------|----------------------------------------------------------------------------------------|-------------------|----------------------------|
|   | SCC2106-04DS | 6.0" |        | 150                 | 32               | 120                    | 185                  | TPU            | PA               | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel                         | 30°<br>or<br>45°  | Φ32x50                     |
|                                                                                    | SCC2108-04DS | 8.0" |        | 200                 | 38.5             | 160                    | 229                  |                |                  |                     |                                                                                        |                   |                            |
|                                                                                    | SCC2106-04TS | 6.0" |        | 150                 | 32               | 120                    | 185                  |                |                  |                     | Three Functions:<br>1. Free Swivel, 2.<br>Direction Lock, 3. Locks<br>Wheel and Swivel | 30°<br>or<br>45°  |                            |
|                                                                                    | SCC2108-04TS | 8.0" |        | 200                 | 38.5             | 160                    | 229                  |                |                  |                     |                                                                                        |                   |                            |
|  | SCC2106-04DL | 6.0" |        | 150                 | 32               | 120                    | 185                  | TPU            | PA               | Double Ball Bearing | Two Functions:<br>1. Free Swivel,<br>2. Locks Wheel and Swivel                         | 30°<br>or<br>45°  | Φ28x96                     |
|                                                                                    | SCC2108-04DL | 8.0" |        | 200                 | 38.5             | 160                    | 229                  |                |                  |                     |                                                                                        |                   |                            |
|                                                                                    | SCC2106-04TL | 6.0" |        | 150                 | 32               | 120                    | 185                  |                |                  |                     | Three Functions:<br>1. Free Swivel, 2.<br>Direction Lock, 3. Locks<br>Wheel and Swivel | 30°<br>or<br>45°  |                            |
|                                                                                    | SCC2108-04TL | 8.0" |        | 200                 | 38.5             | 160                    | 229                  |                |                  |                     |                                                                                        |                   |                            |